



Change for Life

Submittal Data : IDU Gree Slim Ducted **GFH<24>EA-D3DNA1A/I**

Job Name : _____ Date : _____

Engineer : _____ Submitted to : _____

Location : _____ Submitted by : _____

Tag # : _____ Schedule / Drawing # : _____

For : Reference Approval Construction

GENERAL FEATURES

- * Quite Operation - Multi-Speed Fan
- * Medium Static Pressure Capablity
- * Slim Line Construction 7 - 7/8 in. high
- * Internal Condensate Drain Pump
- * Flexible Return air from bottom or rear.
- * Wired Remote Controller
- * Flare connection
- * Condensate Overflow Protection



(Picture is for representation purpose and actual shape may vary)

Cooling	Air Flow
---------	----------

Cooling Capacity	23,800 Btu/h	Air Flow Volume	588.5/ /441.375/ /323.675/ CFM
Cooling fan motor Speed	985/800/680 r/min	Sound Pressure Level	42/ /38/ /34/ dB(A)
Recommended Power Cable(Core)	4	Sound Power Level	52/ /48/ /44/ dB(A)
Cross-sectional Area of Power Cable Conductor	AWG18<0.82>		

Electrical	
------------	--

Heating	
Power supply	230V-1Ph -60Hz
Heating Capacity	27,400 Btu/h
Fuse Current	3.15 A
Fan Motor Power Output	22.5 W
Number of fans	4 N

Set Temperature Range ° F	61 ~ 86
---------------------------	---------

Physical & Piping	
-------------------	--

Dimension of Outline (WxDxH)	1100x615x200 mm	Liquid Line connection	3/8 in
Net Weight	31 kg	Gas connection	5/8 in



1-833-666-GREE
www.greevac.ca

Manufacturer has right to change the data without notice, please refer to the name plate of the unit.